Distillation Theory and Its Application to Optimal Design of Separation Units

F. B. Petlyuk



PUBLISHED BY THE PRESS SYNDICATE OF THE UNIVERSITY OF CAMBRIDGE The Pitt Building, Trumpington Street, Cambridge, United Kingdom

CAMBRIDGE UNIVERSITY PRESS
The Edinburgh Building, Cambridge CB2 2RU, UK
40 West 20th Street, New York, NY 10011-4211, USA
477 Williamstown Road, Port Melbourne, VIC 3207, Australia
Ruiz de Alarcón 13, 28014 Madrid, Spain

Dock House, The Waterfront, Cape Town 8001, South Africa

http://www.cambridge.org

© F. B. Petlyuk 2004

This book is in copyright. Subject to statutory exception and to the provisions of relevant collective licensing agreements, no reproduction of any part may take place without the written permission of Cambridge University Press.

First published 2004

Printed in the United States of America

Typefaces Times Ten Roman 10/13 pt. and Gill Sans System L $^{\perp}$ T_EX 2 $_{\varepsilon}$ [TB]

A catalog record for this book is available from the British Library.

Library of Congress Cataloging in Publication Data

Petlyuk, F. B. (Felix B.), 1934-

Distillation theory and its application to optimal design of separation units / F. B. Petlyuk.

p. cm. – (Cambridge series in chemical engineering)

Includes bibliographical references and index.

ISBN 0-521-82092-8 (hardback)

1. Distillation. 2. Distillation apparatus – Design and construction.

I. Title. II. Series.

TP156.D5P45 2004

660'.28425 - dc22

2003058496

ISBN 0 521 82092 8 hardback

Contents

	Prefa	ce	page xiii
	Ackn	owledgments	xvii
		enclature	xix
I.	Phase	Equilibrium and Its Geometric Presentation	1
	1.1	Introduction	1
	1.2	Concentration Space	
	1.3	Phase Equilibrium of Binary Mixtures	1 3 5
	1.4	Phase Diagrams of Three-Component Mixtures	5
	1.5	Residue Curve Bundles of Four-Component Mixtures	8
	1.6	Matrix Description of the Multicomponent Mixture Residue	
		Curve Structure	10
	1.7	Lines, Surfaces, and Hypersurfaces $K_i = K_j$	12
	1.8	Liquid-Liquid-Vapor Phase Diagrams	15
	1.9	Conclusion	17
	1.10	Questions	18
	1.11	Exercises with Software	18
		References	18
2.	Basic	Concepts of Distillation	20
	2.1	Purpose and Process Essence of Distillation	20
	2.1	1. Description of Distillation Process	21
	2.1	.2. System of Algebraic Equations of Distillation	22
	2.2	Geometric Interpretation of Binary Distillation: Reflux and the	
		Number of Trays	23
	2.2	.1. McCabe-Thiele Diagram	23
	2.2	2. Influences of Nonideality	24
	2.3	Geometric Interpretation of Multicomponent Mixture	
		Distillation: Splits	25
	2.4	Trajectory Bundles Under Infinite Reflux: Distillation Diagrams	26
	2.5	Trajectory Bundles Under Finite Reflux	27
	2.6	Minimum Reflux Mode: Fractionation Classes	29
		.1. Binary Distillation	29
	2.6	.2. Distillation of Three-Component Mixtures	31

	2.7	Adiabatic, Nonadiabatic, and Reversible Distillation	32
	2.8	Separation of Azeotropic Mixtures by Distillation Under Two	
		Pressures or Heteroazeotropic and Extractive Distillation	35
	2.9	Is Process Opposite to Distillation Process Possible?	36
	2.10	Mixtures with Limited and Unlimited Separability	37
	2.11	The Problem of Designing Distillation Units	38
	2.12	Questions	38
		References	39
3.	Traie	ctories of Distillation in Infinite Columns Under Infinite Reflux	40
	3.1	Introduction	40
	3.2	Analogy Between Residue Curves and Distillation Trajectories	
		Under Infinite Reflux	41
	3.3	Distillation Trajectories of Finite and Infinite Columns at Set	
		Feed Composition	43
	3.3	.1. Dimensionality of Product Composition Regions for Finite	
		and Infinite Columns	43
	3.3	.2. Product Composition Regions for Ideal Three-Component	
		Mixtures	44
	3.3	3. Product Composition Regions for Ideal Four-Component	
		Mixtures	45
		.4. Feasible Splits for Ideal Mixtures	47
	3.3	.5. Product Composition Regions for Azeotropic	40
	2.4	Three-Component Mixtures	48
	3.4	Rule for the Checkup of Azeotropic Mixtures Separability at	50
	2.4	$R = \infty \text{ and } N = \infty$	52
		1. Distillation Trajectories Location at $R = \infty$ and $N = \infty$	52
		2. Application of the Rule of Connectedness	53
		3. n-Component Mixture Foogish Splits at P and N and	55 57
	3.5 3.5	Feasible Splits at $R = \infty$ and $N = \infty$ Method of Product Simpley for Distillation Subregions	57
	3.3	1. Method of Product Simplex for Distillation Subregions $(m = n)$	59
	3.5	.2. Method of Product Simplex for Distillation Subregions	39
	3.3	(m > n)	61
	3.5	3. Algorithm of Product Simplex for <i>n</i> -Component Mixtures	63
	3.6	Separation of Azeotropic Mixtures in Sequence of Columns with	0.5
	3.0	Recycles at $R = \infty$ and $N = \infty$	71
	3.7	Nonsingularity of Separation Products Compositions at $R = \infty$, 1
	5.7	and $N = \infty$	72
	3.8	Conclusion	73
	3.9	Questions	74
	3.10	Exercises with Software	74
		References	75
4.	Traie	ctories of Thermodynamically Reversible Distillation	77
••	4.1	Introduction	77
	4.2	Essence of Reversible Distillation Process and Its Peculiarities	78
	4.2		78
		2. Location of Reversible Distillation Trajectories	79
		3. Sharp and Nonsharp Reversible Distillation of Ideal	,,
	2	Mixtures	80

Contents ix

	4.2.4. Column Sequence of Ideal Mixtures Reversible Distillation	81
	4.2.5. Main Peculiarities of Reversible Distillation Column	82
	4.3 Trajectory Bundles of Sharp Reversible Distillation	83
	4.3.1. Bundles and Regions of Sharp Reversible Distillation	83
	4.3.2. Condition in Tear-Off Points of the Reversible Distillation	
	Trajectories	86
	4.3.3. Possible Product Composition Regions	87
	4.3.4. Necessary Condition of Sharp Reversible Distillation	88
	4.3.5. Liquid and Vapor Flow Rates Changing along the Reversible	00
	Distillation Trajectories	89
	4.4 Diagrams of Three-Component Mixture Reversible Distillation	92
	4.4.1. Calculation of Reversible Distillation Trajectories	92
	4.4.2. Scanning the Sides of the Concentration Triangle	93
	4.5 Trajectories Bundles of Reversible Distillation for	,,,
	Multicomponent Mixtures	93
	4.6 Diagrams of Extractive Reversible Distillation for	,,,
	Three-Component Mixtures	97
	4.6.1. Condition in Tear-Off Points of the Extractive Reversible	,
	Distillation Trajectories	97
	4.6.2. Azeotropic Mixtures	99
	4.7 Trajectory Bundles of Extractive Reversible Distillation for	
	Multicomponent Mixtures	100
	4.8 Boundaries of Nonsharp Reversible Distillation	102
	4.8.1. Three-Component Azeotropic Mixtures	102
	4.8.2. Four-Component Azeotropic Mixtures	105
	4.9 Conclusion	105
	4.10 Questions	105
	4.11 Exercises with Software	106
	References	106
5.	Distillation Trajectories and Conditions of Mixture Separability in	
	Simple Infinite Columns at Finite Reflux	108
	5.1 Introduction	108
	5.2 Calculation of Distillation at Minimum Reflux for Ideal Mixtures	111
	5.2.1. Underwood System of Equations	112
	5.2.2. Evolution of Separation Product Compositions of	
	One-Section Columns at Set Feed Composition	114
	5.2.3. Evolution of Separation Product Compositions of	
	Two-Section Columns at Set Feed Composition	117
	5.3 Trajectory Tear-Off Theory and Necessary Conditions of	
	Mixture Separability	120
	5.3.1. Conditions of Distillation Trajectory Tear-Off at Sharp Splits	120
	5.3.2. Trajectory Tear-Off Regions and Sharp Distillation Regions	123
	5.3.2. Trajectory Tear-Off Regions and Sharp Distillation Regions5.3.3. Necessary Condition of Mixture Separability for the Set Split	123 124
	 5.3.2. Trajectory Tear-Off Regions and Sharp Distillation Regions 5.3.3. Necessary Condition of Mixture Separability for the Set Split 5.4 Structure and Evolution of Section Trajectory Bundles for 	124
	 5.3.2. Trajectory Tear-Off Regions and Sharp Distillation Regions 5.3.3. Necessary Condition of Mixture Separability for the Set Split 5.4 Structure and Evolution of Section Trajectory Bundles for Three-Component Mixtures 	124 126
	 5.3.2. Trajectory Tear-Off Regions and Sharp Distillation Regions 5.3.3. Necessary Condition of Mixture Separability for the Set Split 5.4 Structure and Evolution of Section Trajectory Bundles for Three-Component Mixtures 5.4.1. The Product Is a Pure Component (k = 1) 	124 126 126
	 5.3.2. Trajectory Tear-Off Regions and Sharp Distillation Regions 5.3.3. Necessary Condition of Mixture Separability for the Set Split 5.4 Structure and Evolution of Section Trajectory Bundles for Three-Component Mixtures 5.4.1. The Product Is a Pure Component (k = 1) 5.4.2. The Product Is a Binary Mixture (k = 2) 	124 126 126 129
	 5.3.2. Trajectory Tear-Off Regions and Sharp Distillation Regions 5.3.3. Necessary Condition of Mixture Separability for the Set Split 5.4 Structure and Evolution of Section Trajectory Bundles for Three-Component Mixtures 5.4.1. The Product Is a Pure Component (k = 1) 	124 126 126

x Contents

	5.5 Structure and Evolution	ution of Section Trajectory Bundles for	
	Four- and Multico	mponent Mixtures	141
	5.5.1. Four-Componen	t Mixture	141
	5.5.2. Mixtures with A	ny Number of Components	147
	5.6 Conditions of Section	on Trajectories Joining and Methods of	
	Minimum Reflux (Calculating	150
	5.6.1. Two Models of F	Feed Tray	150
	5.6.2. Conditions of Se	ection Trajectories Joining	151
	5.6.3. Direct and Indir	ect Splits (One of the Products Is Pure	
	Component or Az	eotrope)	152
	5.6.4. Intermediate Sp.	lits	154
	5.6.5. Splits with Distri	ibuted Component	158
	5.6.6. Equations of The		161
	5.6.7. Visualization of	Section Trajectories	162
	5.7 Necessary and Suffi	cient Conditions of Separability	
	of Mixtures		162
	5.7.1. Adiabatic Colun		162
	5.7.2. Nonadiabatic Co	olumns	163
	5.8 Conclusion		164
	5.9 Questions		165
	5.10 Exercises with Soft	ware	166
	References		166
6.	Distillation Trajectories	in Infinite Complex Columns	
٠.	and Complexes	in minice complex columns	170
	6.1 Introduction		170
		mediate Inputs and Outputs of Heat:	170
	"Pinch Method"	mediate impair and carpair of freun	172
		ories and Minimum Reflux Mode in Two-Feed	
		nsharp Separation in Intermediate Section	174
		ersible Distillation Trajectories of	
	Intermediate Secti		175
		Trajectory Bundles of Intermediate Sections	177
	6.3.3. Control Feed at		178
	6.3.4. General Algorit	hm of Calculation of Minimum Reflux Mode	179
		rmediate Sections of Extractive Distillation	
	Columns		181
	6.4.1. Sharp Extractive	e Distillation of Three-Component Mixtures	181
	6.4.2. Sharp Extractive	Distillation of Four- and Multicomponent	
	Mixtures	-	186
	6.5 Conditions of Separ	rability in Extractive Distillation Columns and	
	Minimum Reflux I	Mode	187
	6.5.1. Conditions of Se	parability in Extractive Distillation Columns	187
	6.5.2. Three-Compone	ent Mixtures	188
	6.5.3. The Four- and M	Iulticomponent Mixtures	190
	6.6 Determination of M	Inimum Flow Rate of Entrainer	193
	6.7 Distillation Comple	exes with Thermal Coupling Flows	195
	6.7.1. Kinds of Distilla	tion Complexes with Thermal Coupling	
	Flows		195

Contents xi

	6.7.2. Petlyuk Columns	197
	6.8 Calculation of Minimum Reflux Mode for Distillation Complexes	
	with Thermal Coupling Flows	200
	6.8.1. The Columns with Side Withdrawals of Flows	200
	6.8.2. The Columns with Side Strippings	202
	6.8.3. The Petlyuk Columns	204
	6.9 Distillation Trajectories in Complexes of Heteroazeotropic and	
	Heteroextractive Distillation	206
	6.9.1. Heteroazeotropic Distillation	207
	6.9.2. Heteroextractive Distillation	210
	6.10 Conclusion	212
	6.11 Questions	213
	References	213
7.	Trajectories of the Finite Columns and Their Design Calculation	218
••	7.1 Introduction	218
	7.2 Distillation Trajectories of Finite Columns: Possible	210
	Compositions in Feed Cross Section	220
	7.2.1. Location of Section Trajectories	220
	7.2.2. Possible Compositions in Feed Cross Section	223
	7.3 Design Calculation of Two-Section Columns	226
	7.3.1. Direct and Indirect Splits of Mixtures with Any Number of	
	Components	226
	7.3.2. Intermediate Splits of Mixtures with Any Number of	
	Components	227
	7.3.3. Splits with a Distributed Component	239
	7.3.4. Splits with Several Distributed Components: Preferred Split	242
	7.3.5. Advantages of New Design Algorithms	243
	7.4 Design Calculation of Extractive Distillation Columns	243
	7.4.1. Three-Component Azeotropic Mixtures	245
	7.4.2. The Multicomponent Mixtures: The Top Product and the	
	Entrainer Are Pure Components $(m_r = 1, m_e = 2)$	246
	7.4.3. The Multicomponent Mixtures: The Top Product Is a Binary	
	Mixture, the Entrainer Is a Pure Component $(m_r = 2, m_e > 2)$	247
	7.4.4. The Multicomponent Mixtures: The Top Product Is a Pure	
	Component, the Entrainer Is a Mixture $(m_r = 1, m_e > 2)$	247
	7.5 Design Calculation of "Petlyuk Columns" and of Columns with	
	Side Sections	249
	7.5.1. Design Calculation of "Petlyuk Columns"	249
	7.5.2. Design Calculation of Columns with Side Sections	252
	7.6 Determination of Necessary Tray Numbers at Heteroazeotropic	
	and Heteroextractive Distillation	255
	7.7 Conclusion	257
	7.8 Questions	259
	7.9 Exercises with Software	259
	References	260
8.	Synthesis of Separation Flowsheets	263
٠.	8.1 Introduction	263
	8.2 Zeotropic Mixtures	265
	5.2	200

8.2.1. Heuristic Rules of Synthesis	265
8.2.2. Estimation of the Expenditures on Separation	265
8.2.3. Preferability Regions for Ternary Mixtures	267
8.2.4. Systematic Identification of Alternative Sequences	269
8.2.5. Examples of Synthesis of Separation Flowsheets	271
8.3 Thermodynamically Improved and Thermally Integrated	
Separation Flowsheets	276
8.3.1. Thermodynamic Losses and Their Decrease	276
8.3.2. Thermally Integrated Separation Flowsheets	279
8.3.3. The Heat Pump	279
8.4 Multicomponent Azeotropic Mixtures: Presynthesis	281
8.4.1. Possible Product Segments at the Edges of Concentration	
Simplex	282
8.4.2. Possible Product Regions at the Boundary Elements of	
Concentration Simplex	283
8.4.3. Possible Sharp Splits in Columns with One Feed	286
8.4.4. Possible Sharp Splits in Columns with Two Feeds	287
8.4.5. The Most Interesting Splits of Columns with Decanters	288
8.4.6. Examples of Presynthesis	288
8.4.6.1. Example 1: Simple Columns	288
8.4.6.2. Example 1: Extractive Distillation	290
8.4.6.3. Example 2: Simple Columns	292
8.4.6.4. Example 2: Extractive Distillation	299
8.5 Multicomponent Azeotropic Mixtures: Automatic Sequencing	
and Selection	300
8.5.1. Selection of Splits	301
8.5.2. Examples of Sequencing and Selection	303
8.5.2.1. Example 1	303
8.5.2.2. Example 2	305
8.6 Binary and Three-Component Azeotropic Mixtures	307
8.6.1. Application of Semisharp Extractive Distillation	307
8.6.2. Application of Pressure Change	308
8.6.3. Choice of Entrainers	309
8.7 Petroleum Mixtures	312
8.7.1. Peculiarities of Petroleum as Raw Material for Separation	312
8.7.2. Methods of Petroleum Separability Increase	312
8.7.3. The Best Distillation Complex for Petroleum Refining	313
8.7.4. Main Succession of Petroleum Refining	314
8.7.5. Modernization of Units for Petroleum Refining	317
8.8 Conclusion	318
8.9 Questions	319
References	320
Short Glossary	325
Index	329

Phase Equilibrium and Its Geometric Presentation

I.I. Introduction

The process of distillation can be presented as consisting of numerous states of phase equilibrium between flows of liquid and vapor that have different compositions. Geometric analysis of the distillation process represented in the so-called $concentration\ space\ (C)$ is the main instrument for understanding its regularities.

That is why, before we start the examination of the existing distillation process and its geometric interpretation, it is necessary to consider geometric interpretation, of the phase equilibrium. Numerous methods of calculating phase equilibrium are described in many monographs and manuals (see, e.g., Walas [1985]).

We will not repeat these descriptions but instead will examine only representation of equilibrium states and processes in concentration space.

I.2. Concentration Space

Molar composition of an *n*-component mixture is presented as an array that holds molar concentrations of all components:

$$x_i = \frac{m_i}{\sum m_i} \tag{1.1}$$

$$\sum x_i = 1 \tag{1.2}$$

where m_i is the amount of moles of the component i in the mixture.

Concentration space of an n-component mixture C_n is a space in which every point corresponds to a mixture of definite composition. Dimensionality of concentration space corresponds to the number of concentrations of components that can be fixed independently.

The (n-1) concentration for an n-component mixture can be fixed independently because concentration of the nth component can be found from Eq. (1.2). That is why the dimensionality of the concentration space of binary mixture C_2 is one, of ternary mixture C_3 – two, of four-component mixture C_4 – tree, etc.

2 Phase Equilibrium and Its Geometric Presentation




Figure 1.1. Concentration simplexes (a) for binary mixtures, (b, c) for three-component mixtures. and (d) for four-component mixtures. x_1, x_2, x_3, x_4 , concentrations of components.

Concentration space is the number of points representing all possible compositions of an n-component mixture. Concentration space of a binary mixture C_2 is a segment of unit length; the ends correspond to pure components, and the inner points correspond to mixtures of various compositions (Fig. 1.1a)

For a three-component mixture, it is convenient to present the composition space C_3 as an equilateral triangle, the height of which equals one (Fig. 1.1b). The triangle's vertexes represent pure components, the points within its sides, represent the binary constituents of the three-component mixture, and the inner points of triangle represent the three-component mixture compositions. The lengths of the perpendiculars to the triangle's sides correspond to the concentrations of the components indicated by the opposite vertexes. The described system of coordinates, which bears the name of the system of uniform coordinates, was introduced by Mobius and was further developed by Gibbs.

Another way to present a three-component mixture's composition space C_3 implies the use of an isosceles right-angle triangle (Fig. 1.1c), with a side equal to one. In this method of representation the concentrations of components 1 and 2 are expressed by the length of perpendicular segments, as in the first case of the composition's representation, and the concentration of the third component is defined in accordance with the formula: $x_3 = 1 - (x_1 + x_2)$.

Four-component mixture composition can be represented by a point of an equilateral tetrahedron C_4 (Fig. 1.1d). In this tetrahedron the vertexes represent the pure components, the edges represent the binary constituents, and the faces represent the three-component constituents.

In this book, we will often represent the mixture compositions corresponding to the material balance (e.g., the compositions of feed flow and product flow of the distillation column):

$$Fx_{iF} = Dx_{iD} + Bx_{iB} ag{1.3}$$

$$(D+B)x_{iF} = Dx_{iD} + Bx_{iB} \tag{1.4}$$

$$D(x_{iF} - x_{iD}) = B(x_{iB} - x_{iF})$$
(1.5)

Equation (1.5) represents the so-called *lever rule*: points x_{iF} , x_{iD} , and x_{iB} are located on one straight line, and the lengths of the segments $[x_{iF}, x_{iD}]$ and $[x_{iB}, x_{iF}]$ are inversely proportional to the flow rates D and B (Fig. 1.1b). Mixture with a component number $n \ge 5$ cannot be represented clearly. However, we will apply the terms simplex of dimensionality (n-1) for a concentration space of n-component mixture C_n , hyperfaces C_{n-1} of this simplex for (n-1)-component constituents of this mixture, etc.

1.3. Phase Equilibrium of Binary Mixtures

An equilibrium between liquid and vapor is usually described as follows:

$$y_i = K_i x_i \tag{1.6}$$

where y_i and x_i are equilibrium compositions of vapor and liquid, respectively, and K_i is the liquid-vapor phase equilibrium coefficient.

To understand the mutual behavior of the components depending on the degree of the mixture's nonideality caused by the difference in the components' molecular properties, it is better to use graphs $y_1 - x_1$, $T - x_1$, $T - y_1$, $K_1 - x_1$, and $K_2 - x_1$ (Fig. 1.2). In Fig. 1.2, the degree of nonideality increases from a to h: a is an ideal mixture, b is a nonideal mixture with an *inflection on the curve* $y_1 - x_1$ (a and b are zeotropic mixtures), c is a mixture with a so-called *tangential azeotrope* (curve $y_1 - x_1$ touches the diagonal in the point $x_1 = 1$), d is an *azeotropic mixture* with minimum temperature, e is a mixture with a so-called *inner tangential azeotrope*, f is a *mixture with two azeotropes*, g is a *heteroazeotropic mixture*, and g is an *azeotropic mixture with two liquid phases*. *Azeotrope* is a binary or multicomponent mixture composition for which the values of phase equilibrium coefficients for all components are equal to one:

$$K_i^{Az} = 1 (i = 1, 2, ...n)$$
 (1.7)

Heteroazeotrope is an overall composition of a mixture with two liquid phases for which the values of the overall coefficients of phase equilibrium for all components are equal to one:

$$K_{ov,i}^{Haz} = 1$$
 $(i = 1, 2, ...n)$ (1.8)

where $K_{ov,i} = y_i/x_{ov,i}$, $x_{ov,i} = x_i^{(1)}a + x_i^{(2)}(1-a)$, a is the portion of the first liquid phase in the whole liquid, and $x_i^{(1)}$ and $x_i^{(2)}$ are the concentrations of the ith component in first and second liquid phases correspondingly.

In this book, we will see that the previously discussed features are of great importance. Even b case results in serious abnormalities of the distillation process.

4 Phase Equilibrium and Its Geometric Presentation




Figure 1.2. Phase equilibrium of binary mixtures: (a) ideal mixture; (b) nonideal mixture; (c) tangential azeotropic mixture $(x_1, A_z = 1)$; (d) azeotropic mixture; (e) mixture with internal tangential azeotrope $(0 < x_1, A_z < 1)$; (f) mixture with two azeotropes Az_1 and Az_2 ; (g) heteroazeotropic mixture; and (h) azeotropic mixture with two liquid phases (y - x, T - x - y, and K - x diagrams). Az, azeotropic or heteroazeotropic point; x_{L1} and x_{L2} , compositions of liquid phases.

The appearance of azeotropes makes the separation of the mixture into pure components impossible without special procedure application.

Further increase in nonideality and transition to heteroazeotropes makes it again possible to separate mixtures, not using just a distillation column, but a *column with decanter* complex. Cases e and f occur, but very seldom; therefore, we will not consider them further.

In the azeotrope point, $K_1 = K_2 = 1$. For a tangential azeotrope, $x_1^{Az} = 1$ or $x_1^{Az} = 0$. It might seem that a tangential azeotrope is no obstacle for separation.

However, later in this book, we will see that if $x_1^{Az} = 1$, it is impossible to get component 1 with a high degree of purity, and if $x_1^{Az} = 0$, it is impossible to get component 2 with a high degree of purity.

1.4. Phase Diagrams of Three-Component Mixtures

Three-component mixtures represent the simplest type of multicomponent mixtures. The majority of multicomponent mixture peculiarities become apparent in three-component mixtures. This is why the three-component mixtures are best studied. Liquid-vapor equilibrium in the concentration triangle C_3 is represented by a vector connecting a point of liquid composition with a point of equilibrium vapor composition $x \to y$. This vector is called a *liquid-vapor tie-line*. The opposite vector $y \to x$ (vapor-liquid) is called a *vapor-liquid tie-line*. The tie-lines field in the concentration triangle characterizes phase equilibrium in each of its points.

However, tie-lines can cross each other. That is why, for phase equilibrium characteristics in the concentration space, it is convenient to use another kind of line, the so-called *residue curves*. Let's consider a process of *open evaporation* (*simple distillation*) illustrated in Fig. 1.3.

Let's assume that the initial amount of liquid in a flask makes L moles and the liquid has a composition x_i (i = 1, 2, ... n). After the evaporation of a small amount of liquid ΔL , vapor with a composition y_i (i = 1, 2, ... n), will be formed which represents an equilibrium of the remaining liquid, the amount of which is equal to $L - \Delta L$ moles and the composition is $x_i + \Delta x_i$.

The material balance for *i* component is:

$$Lx_i = (\Delta L)y_i + (L - \Delta L)(x_i + \Delta x_i)$$
(1.9)

In limit at $\Delta L \rightarrow 0$,

$$Ldx_i/dL = x_i - y_i (1.10)$$




Figure 1.3. Open evaporation process (open distillation). x, y, composition of liquid and equilibrium vapor phases; L, amount of liquid; dL, infinitesimal amount of evaporated liquid.

Denoting dt = dL/L, we will get the equation of a residue curve:

$$dx_i/dt = x_i - y_i$$
 $(i = 1, 2, ...n)$ (1.11)

The residue curve represents the change in a mixture composition during the open evaporation process. Each point of this line corresponds to a certain moment of time and to a portion of evaporated liquid.

From Eq. (1.11), it results that in each point of a residue curve a liquid–vapor tie-line is tangent to this line. The residue curves are convenient for the description of phase equilibrium because as these lines are continuous and noncrossing.

These lines were used for the first time to describe phase behavior of three-component azeotropic mixtures at the beginning of the twentieth century (Ostwald, 1900; Schreinemakers, 1901). Later, the residue curves of three-component azeotropic mixtures were studied in the works of Reinders & De Minjer (1940a, 1940b) for the azeotropic mixture acetone–chloroform–benzene and more widely in the works by Bushmakin & Kish (1957a, 1957b). Gurikov (1958) developed the first classification of three-component mixtures residue curve diagrams. In the works of Zharov (1967, 1968a, 1968b) and Serafimov (1969) the residue curve diagrams analysis and classification were applied for four-component and multicomponent mixtures. Several years later, these works were summarized in a monograph by Zharov & Serafimov (1975). In recent years, other versions of residue curve diagram classifications were developed (Matsuyama & Nishimura, 1977; Doherty & Caldarola, 1985).

Points of pure components and azeotropes are stationary or singular points of residue curve bundles. At these points, the value dx_i/dt in Eq. (1.11) becomes equal to zero. A stationary point at which all residue curves come to an end is called a stable node (the temperature increases in the direction of this point). A specific point at which all residue curves start is called an unstable node (the temperature




Figure 1.4. Types of stationary points of three-component mixtures: (a) one-component stable node, (b) one-component unstable node, (c) one-component stable node, (e) two-component unstable node, (f) two-component saddle, (g) three-component stable node, (h) three-component unstable node, and (i) three-component saddle. Arrows, direction of residium curves.

increases in the opposite direction of this point). The rest of stationary points are called *saddles* (Fig. 1.4).

A stationary point type is defined by the *proper values* of Yakobian from Eq. (1.11). For a stable node, both proper values are negative, $\lambda_1 < 0$ and $\lambda_2 < 0$; for an unstable node, both proper values are positive, $\lambda_1 > 0$ and $\lambda_2 > 0$; and for a saddle, one proper value is negative, $\lambda_1 < 0$, and the second is positive, $\lambda_2 > 0$.

For a distillation process not only the stationary point type, but also the behavior of the residue curve in the vicinity of the stationary point is of special importance. If the residue curves in the vicinity of the specific point are tangent to any straight line (singular line) (Fig. 1.4a, b, d, e, g, h), the location of this straight line is of great importance. A special point type and behavior of residue curves in its vicinity are called stationary point *local characteristics*.

The whole concentration space can be filled with one or more residue curve bundles. Each residue curve bundle has its own initial point (unstable node) and its own final point (stable node). Various bundles differ from each other by initial or final points.

The boundaries separating one bundle from another are specific residue curves that are called the *separatrixes of saddle stationary points*. In contrast to the other residue curves, the separatrixes begin or come to an end, not in the node points but in the saddle points. A characteristic feature of a separatrix is that in any vicinity of its every point, no matter how small it is, there are points belonging to two different bundles of residue curves. The concentration space for ideal mixtures is filled with one bundle of residue curves. Various types of azeotropic mixtures differ from each other by a set of stationary points of various types and by the various sequence of boiling temperatures in the stationary points.

The first topological equation that connects a possible number of stationary points of various types for three-component mixtures (*N*, node; *S*, saddle; upper index is the number of components in a stationary point) was deduced (Gurikov, 1958):

$$2(N^3 - S^3) + N^2 - S^2 + N^1 = 2 (1.12)$$

Figure 1.5 shows mainly physically valuable *types of three-component azeotropic mixtures* deduced by Gurikov (1958) by means of systematic application of Eq. (1.12). In Fig. 1.5, one and the same structure cover a certain type of mixture and an antipodal type in which stable nodes are replaced by unstable ones and vice versa (i.e., the direction of residue curves is opposite). Besides that, the separatrixes are shown by the straight lines. Let's note that the later classifications of three-component mixture types (Matsuyama & Nishimura, 1977; Doherty & Caldarola, 1985) contain considerably greater number of types, but many of these types are not different in principle because these classifications assume light, medium, and heavy volatile components to be the fixed vertexes of the concentration triangle.

Types of azeotropic mixture and separatrixes arrangements are also called mixture *nonlocal characteristics*.

The part of the concentration space filled with one residue curve bundle is called a distillation region $\operatorname{Reg}^{\infty}$ (Schreinemakers, 1901). A distillation region $\operatorname{Reg}^{\infty}_{(3)}$ has






Figure 1.5. Types of three-component mixtures according to Gurikov (1958). Arrows, direction of residium curves (bonds); dotted lines, separatrixes.

boundary elements that include the separatrixes, segments of the concentration triangle sides $\operatorname{Reg}_{(2)}^{\infty}$, and stationary points $\operatorname{Reg}_{(1)}^{\infty}$ referring to this region. A distillation region of a three-component mixture $\operatorname{Reg}_{(3)}^{\infty}$ is *two-dimensional*; separatrixes, and segments of the concentration triangle sides $\operatorname{Reg}_{(2)}^{\infty}$ are *one-dimensional*; and stationary points $\operatorname{Reg}_{(1)}^{\infty}$ have *zero dimensionality*. Distillation regions and their boundary elements are also called concentration space *structural elements*.

Besides these structural elements, concentration space has other structural elements that are of great importance for a distillation process under various modes.

1.5. Residue Curve Bundles of Four-Component Mixtures

The structure of residue curve bundles of four-component mixtures is significantly more complex and diverse than that of three-component mixtures. This is due to the fact that each four-component mixture consists of four three-component constituents. Therefore, the number of types of four-component mixtures is enormous. In addition to that, four-component mixtures can have four-component node and saddle azeotropes. In contrast to three-component mixtures, the enormous




Figure 1.6. Types of saddle points of four-component mixtures: (a) one-component saddle, (b, c) two-component saddle, (d, e) three-component saddle, and (f) four-component saddle. Separatrix surfaces are shaded. Arrows, direction of residium curves; dotty lines, separatrixes.

number of four-component mixture structures makes their overall sorting out practically impossible. However, a topological equation for four-component mixtures similar to Eq. (1.12) was obtained (Zharov & Serafimov, 1975).

To understand the peculiarities of location of residue curve bundles of four-component mixtures, let's consider their behavior in the vicinity of saddle points (Fig. 1.6) and the nonlocal characteristics of the residue curve bundles using separate examples of the four-component mixture structures (Fig. 1.7). In Fig. 1.7, the separating surfaces of the residue curve bundles representing the two-dimensional bundles $\text{Reg}_{(3)}^{\infty}$ are shaded. Considering the nonlocal characteristics of the residue curve bundles, the simplest of such characteristics refers to each pair of stationary points. A pair of stationary points can be connected or not connected by the residue curve. To be brief, let's call the line of distillation that connects a pair of stationary points a bond (link) – it will be designated by the arrow (\rightarrow) that is directed toward the side of the temperature increase (Petlyuk, Kievskii, & Serafimov, 1975a, 1975b, 1977, 1979). For example, in Fig. 1.7a, 12 \rightarrow 23. In the same figure, points 1 and 2 are not bonded.

The totality of all bonds characterizes the mixture's structure. The bond serves as the *elementary nonlocal characteristic* of the residue curve bundle structure. Bonds form bond chains. The *bond chains* of maximum length connect the unstable node N^- and the stable node N^+ of the distillation region $\operatorname{Reg}^{\infty}$. Let's call a polyhedron formed by all stationary points of one maximum-length bond chain and containing all components of the mixture a *distillation subregion* Reg_{sub} .

The distillation region Reg^{∞} is a polyhedron formed by all stationary points of the totality of all maximum-length bond chains connecting the same unstable node of the composition space with the same stable node (it will be designated \Rightarrow). The examples of distillation regions Reg^{∞} are $12 \Rightarrow 4$, $12 \Rightarrow 2$ (at Fig. 1.7a),






Figure 1.7. The examples of four-component structures (bonds and distillation regions Reg^{∞}). Separatrix surfaces are shaded. Arrows, direction of residium curves; dotty lines, separatrixes.

 $1 \Rightarrow 4, 1 \Rightarrow 2, 23 \Rightarrow 4, 23 \Rightarrow 2$ (at Fig. 1.7b), $1 \Rightarrow 3, 1 \Rightarrow 4, 2 \Rightarrow 3, 2 \Rightarrow 4$ (at Fig. 1.7c), $13 \Rightarrow 1, 13 \Rightarrow 3, 2 \Rightarrow 1, 2 \Rightarrow 3$ (at Fig. 1.7d), $134 \Rightarrow 1, 4 \Rightarrow 1$ (at Fig. 1.7e), $23 \Rightarrow 2, 23 \Rightarrow 3, 4 \Rightarrow 2$, and $4 \Rightarrow 3$ (at Fig. 1.7f).

The examples of distillation subregions Reg_{sub} are $12 \to 23 \to 3 \to 4$, $12 \to 1 \to 3 \to 4$, and $12 \to 23 \to 24 \to 4$ (Fig. 1.7a). In this case, the distillation region $\operatorname{Reg}^{\infty}$ is $12 \Rightarrow 4$ ($\operatorname{Reg}_{sub} \in \operatorname{Reg}^{\infty}$), or

$$\uparrow \rightarrow 1 \rightarrow \downarrow
12 \rightarrow 23 \rightarrow 3 \rightarrow 4
\downarrow \rightarrow 24 \rightarrow \uparrow$$

As we will see in Chapter 3, the distillation region and subregion characterize those possible product compositions that can be produced from the given feedstock composition by distillation under one of the most important modes, in particular, under the *infinite reflux mode*.

A bond, bond chain, distillation subregion, and region are the nonlocal structural elements of the azeotropic mixture concentration space.

1.6. Matrix Description of the Multicomponent Mixture Residue Curve Structure

The structure of the residue curve bundles can be obviously represented only for binary, three-, and four-component mixtures. For mixtures with more components, it is impossible. However, practice needs make necessary the analysis of the bundle structure with any number of components. This problem can be solved by means of a structure matrix description (Petlyuk et al., 1975a, 1975b).




Figure 1.8. The examples of three-component structures and their structural matrices. Arrows, direction of residium curves; dotted lines, separatrixes; thick line with arrow, bond; dotty lines, transfer to next bond.

By the *structural matrix* of the azeotropic mixture concentration space, we will name a square matrix, the columns and lines of which correspond to the stationary points and the elements of which $a_{ij} = 1$, if there is a bond directed from stationary point i to stationary point j ($a_{ij} = 0$, if such a bond is missing). For the purpose of obviousness, some examples of three-component mixture structural matrices are shown in Fig. 1.8.

Each line of a structural matrix corresponds to the *i*th stationary point and each column to the *j*th one. Diagonal elements $a_{ij} = 1$ (it is accepted conditionally that each specific point is bonded to itself). The components are labeled 1, 2, 3; binary azeotropes are designated by two-digit numbers, 12, 13, 23; and the ternary azeotrope by a three-digit number, 123. Zero column corresponds to an unstable node N^- and zero line to the stable N^+ one (except for the diagonal elements). Structural matrices provide an opportunity to easily single out all maximum-length

bond chains (i.e., all the distillation subregions). For example, in Fig. 1.8c, the distillation subregions Reg_{sub} are as follows: $123 \to 12 \to 1$, $123 \to 13 \to 1$, $123 \to 12 \to 2$, $123 \to 23 \to 2$, $123 \to 23 \to 3$, and $123 \to 13 \to 3$. Respectively, the distillation regions Reg_{20} are as follows: $123 \to 1$, $123 \to 2$, $123 \to 3$, or

$$\uparrow \rightarrow 13 \rightarrow \downarrow, \uparrow \rightarrow 23 \rightarrow \downarrow, \uparrow \rightarrow 13 \rightarrow \downarrow
123 \rightarrow 12 \rightarrow 1123 \rightarrow 12 \rightarrow 2123 \rightarrow 23 \rightarrow 3$$

1.7. Lines, Surfaces, and Hypersurfaces $K_i = K_i$

In Sections 1.3 to 1.5, the residue curve bundles, which characterize the direction of liquid–vapor tie-lines in each point of the concentration space (i.e., the phase equilibrium field), were considered. As stated previously, such characteristics of the phase equilibrium field and structural elements related to it (bonds, distillation regions, and subregions) are the most important for one of the distillation modes, in particular, for the infinite reflux mode.

However, the liquid–vapor phase equilibrium field has other important characteristics that become apparent under other distillation modes, in particular, under *reversible distillation* and usual (adiabatic) *distillation with finite reflux*.

To such characteristics are referred, first of all, lines, surfaces, and hypersurfaces of the phase equilibrium coefficients equality $(K_i = K_j)$. For the purpose of brevity, we will name these lines, surfaces, and hypersurfaces as α -lines, α -surfaces, and α -hypersurfaces (or univolatility lines, surfaces, and hypersurfaces: $\alpha_{ij} = K_i/K_j = 1$).

Univolatility α -lines, α -surfaces, and α -hypersurfaces divide the concentration simplex into regions of order of components Reg_{ord} (in $\operatorname{Reg}_{ord} K_i > K_j > K_k$) (Petlyuk & Serafimov, 1983).

The totality of several regions of components' order for which one and the same component appear to be the most light volatile ($K_l = \max_i K_i$) or the most heavy volatile ($K_h = \min_i K_i$) was named as a region of reversible distillation $\operatorname{Reg}_{rev, s}^l$ or $\operatorname{Reg}_{rev, r}^h$ (Petlyuk, 1978). Such a name can be explained by the crucial meaning of these regions for possibly realizing of reversible distillation (see Chapter 4).




Figure 1.9. α -lines, α -surfaces (shaded), and regions of order of components Reg_{ord} for (a) three-component and (b) four-component mixtures. 231, 213, 2431, and 2413, regions of component order Reg_{ord} , Reg_{ord} , Reg_{ord} , and Reg_{ord} ; $x \to y$, tie-line liquid-vapor for point x on α -line; arrows, direction of residium curves; dotty lines, separatrixes.